

CHRONO CARBON R 29, CHERRY RED/CARBON, 2022

obj. č: 010.22024



Sugerowana cena

14.559 zł

Specyfikacje techniczne

produkowane rozmiary S: 395mm / M: 430mm / L: 470mm / XL: 520mm	rama Chrono 29 Stealth full Carbon, XC Forward Geometry, 73mm BSA bottom bracket, tapered head tube, HHG Internal Cable routing, Boost 12x148mm rear axle, Comfort Flat chainstays (Flatstays) design
widelec Rockshox SID SL Base RL 29, 100mm, Charger, Debonair, tapered steerer tube, Boost 15x110mm axle, 32mm aluminum stanchions, offset 44mm. Settings: OneLock 2 position remote compression (open/lock), low-speed rebound, air preload	stery Onoff Titan tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41.8x30.5x8x45°x45°, bottom 51.9x40x8x45°x45°
przerzutka Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1	manetki Sram Trigger NX Eagle, 12s, X-Actuation 1:1
klamki hamulca Sram Level, tooled reach adjust, lever pivot bushings	uchwyty Truvativ Stylo 6K Eagle, 12s, Boost, DUB axle, Direct Mount chain ring, S size: 170mm, M/L/XL size: 175mm
support Sram DUB BSA, sealed bearings, 73mm	kierownica Onoff Sulfur 0.2, double butted 6061 alloy, rise: 4.8mm, width: 760mm, 9° backsweep, 0° upsweep, 31.8mm barbore
mostek MDK, 6061 T6 Alloy, 31.8mm barbore, rise: +/-5°, length: size S: 60mm, size M: 70mm, size L: 80mm, size XL: 90mm	sztolica Onoff Sulfur 0-R, 6061 T6 Alloy, 3D forged, diameter 27.2mm, length 400mm
siodełko Mondraker XC Series, steel rail	piasta przednia Mavic, Boost 15x110mm, IS 6 bolts
tylna piasta Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts	łańcuch Sram SX Eagle, 12s, Powerlock
kaseta Sram XG-1230, 11-50T, 12s	szprychy Mavic straightpull duble butted, contactless lacing
rafki Mavic Crossmax 29, 25mm internal width, welded rim, hookless, tubeless ready, 24 spokes	obudowa Maxxis Ikon 29x2.20, 3CMaxx Speed compound, tubeless ready, 120TPI, folding bead, Maxxis Ikon 29x2.20, 3CMaxx Speed compound, tubeless ready, 120TPI, folding bead
zamówienie numer 010.22024	gripy Onoff Sulfur 0.2, double butted 6061 alloy, rise: 4.8mm, width: 760mm, 9° backsweep, 0° upsweep, 31.8mm barbore
przedni hamulec Sram Level T, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad	tylny hamulec Sram Level T, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad

korba
34T, steel, X-Sync 2

mocowanie przerzutki
Mondraker M068

Galeria

