

CRAFTY SE, BLACK/MARLIN BLUE, 2022

obj. č: 010.22220

Sugerowana cena

33.279 zł



Specyfikacje techniczne

produkowane rozmiary S: 380mm / M: 420mm / L: 450mm / XL: 490mm	rama Crafty 6061 Alloy Stealth Evo, e-Bike Optimized Zero Suspension System, 150mm travel, Forward Geometry, internal removable battery with integrated alloy cover, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers.
widelec Fox 38 29 Float FIT GRIP EVOL Performance, 160mm, e-bike tuned, tapered steerer tube, Boost 15x110mm axle, 44mm offset. Settings: 3 positions with micro adjust compression, low-speed rebound, air preload	stery Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°
przerzutka Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1	manetki Sram Trigger NX Eagle, 12s, X-Actuation 1:1, single click
klamki hamulca Sram G2 R, tool-free reach adjust	uchwyty Race Face Aeffect ebike, 165mm
kierownica Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm bar bore	mostek Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm bar bore
sztyca Onoff Pija dropper internal, diameter 31.6mm, S size: 387x125mm, M size: 425x150mm, L/XL size: 465x170mm	siodełko FIZIK Terra Aidon X5 145mm
piasta przednia Mavic, Boost 15x110mm, IS 6 bolts	tylna piasta Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts
łańcuch Sram SX Eagle, 12s, Powerlock	kaseta Sram PG-1210, 11-50T, 12s
szprychy Mavic J-bend double butted, contactless lacing	rafki Mavic E-Deemax 29, 30mm internal width, welded, PFP, tubeless ready, 28 spokes
obudowa Maxxis Minion DHF 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead, Maxxis Minion DHR II 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead	zamówienie numer 010.22220
gripy Onoff Diamond, 1 lock-on, 135mm	amortyzator Fox Float-X LV Performance, 205x65mm. Settings: compression 2 positions lever, low-speed rebound, air preload. Trunnion top mount, 25x10mm bottom bushings

przedni hamulec Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads	tylny hamulec Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads
regulacja amortyzatora medium compression, medium rebound, air volume spacer 0.2	korba Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD
mocowanie przerzutki Mondraker M068	silnik + akumulator Bosch Performance Line CX Cruise (25Km/h) GEN4, Bosch Powertube 625Wh, Bosch Kiox

Galeria

