

Specyfikacje techniczne

produkowane rozmiary One size 260mm	**waga** 12,9 Kg
rama Play 20 6061 Alloy Stealth evo, hydroformed tubing, integrated internal non-removable battery, Tapered head tube, HHG internal cable routing, BSA bottom bracket, QR 9mm rear axle, 1x drivetrain compatible	**widelec** MDK 20 Kid, Rigid alloy Stealth stanchions, Post Mount disc brake mount
stery Onoff Saturn tapered for 1-1/8 to 1-1/2 head tube, ACB sealed bearings, top 41x30.2x7x45x45, bottom 51.9x40x8x45x45	**przerzutka** Shimano Alivio M3100, SGS, Shadow, 9S
manetki Shimano Alivio M3100, Rapid Fire Plus, 9s	**klamki hamulca** Tektro Auriga HDM291 hydraulic
uchwyty Samox, Direct mount chain ring, 155mm	**support** Samox BSA, 73mm
kierownica MDK XC 1.0, 6061 alloy, rise: 25mm, width: 580mm, 9 backsweep, 5 upsweep, 31.8mm barbore Kids	**mostek** MDK XC, 6061 forged alloy, 31.8mm barbore, rise: 0, length: 35mm
sztyca Pivotal	**siodełko** MDK Kids series
piasta przednia Formula DC20LW, 9x100mm, cup cone ball bearings, IS 6 bolts	**tylna piasta** Mahle-Ebikemotion X-35
łańcuch Shimano HG53, 9s	**kaseta** Shimano Alivio HG400, 11-36T, HG, 9s
szprychy CN round stainless steel	**rafki** MDK-XP1 20 TLR, 23mm internal width, tubeless ready, 32 spokes
obudowa Kenda Booster 20x2.4 single compound 30TPI, wire bead	**zamówienie numer** 010.21321
przedni hamulec Tektro Auriga HDM291 hydraulic, 160mm IS 6 bolts rotor	**tylny hamulec** Tektro Auriga HDM291 hydraulic, 160mm IS 6 bolts rotor
owijka Kenda Booster 20x2.4 single compound 30TPI, wire bead	**korba** 28T, steel
mocowanie przerzutki Mondraker M073	**silnik + akumulator** Mahle-Ebikemotion X-35, computer Mahle-Ebikemotion, Mahle-Ebikemotion Internal 250Wh