

PODIUM CARBON RR, CARBON/RED/BLUE, 2021

obj. č: 010.21029



Sugerowana cena

31.199 zł

Specyfikacje techniczne


produkowane rozmiary S 390mm / M 420mm / L 470mm / XL 510mm	waga 8,4 Kg
rama Podium 29 Stealth Air Carbon, XC Forward Geometry, BSA bottom bracket, tapered head tube, HHG internal cable routing, Boost 12x148mm rear axle, dedicated 1X drivetrain design, Flatmount brake compatible,	widelec Rockshox SID SL Ultimate RL 29, 100mm, Charger Race day, Debonair, tapered steerer tube, Boost 15x110mm axle, 32mm aluminum stanchions, offset 44mm. Settings: OneLock 2 position remote compression (open/lock), low-speed rebound, air preload
stery Onoff Titan tapered for 1-1/8 to 1-1/2 head tube, ACB sealed bearings, top 41.8x30.5x8x45x45, bottom 51.9x40x8x45x45	przerzutka Sram X01 Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1
manetki Sram Trigger GX Eagle, 12s, X-Actuation 1:1	klamki hamulca Sram Level TLM, Direct Link actuation, tooled reach adjust, lever pivot bushings
uchwyty Sram X01 Carbon Eagle, Boost, DUB axle, Direct mount chain ring, S size: 170mm, M/L/XL size: 175mm	support Sram DUB BSA, sealed bearings, 73mm
kierownica Onoff Helium Carbon 0.2, rise: 4.8mm, width: 740mm, 9 backsweep, 0 upsweep, 31.8mm barbore Onoff Desert, 1lock-on, 135mm, sizes: S/M L/XL	mostek MDK, 6061 T6 Alloy, 31.8mm barbore, rise: +/-5, length: sizes S/M: 60mm, size L: 70mm, size XL: 80mm
sztyca Onoff Helium Carbon 0-R VFLEX, diameter 27.2mm, length 400mm	siodełko Fizik Antares R7
piasta przednia Mavic Boost 15x110mm, IS 6 bolts	tylna piasta Mavic Boost 12x148mm, 24T Ratchet system, IS 6 bolts, XD freehub
łańcuch Sram GX Eagle, 12s, Powerlock	kaseta Sram XG-1275, 10-50T, 12s
szprychy Mavic steel butted, bladed, straightpull	rafki Mavic Crossmax SLR Carbon 29, 26mm internal width, hookless, UST tubeless, 28 spokes
obudowa Maxxis Ikon 29x2.20, 3CMaxx Speed compound, tubeless ready, 120TPI, folding bead	zamówienie numer 010.21029
przedni hamulec Sram Level TLM, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad	tylny hamulec Sram Level TLM, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad

owijka
Maxxis Ikon 29x2.20, 3CMaxx Speed compound, tubeless ready, 120TPI,
folding bead

korba
34T, CNC-machined alloy, X-SYNC 2

mocowanie przerzutki
Sram UDH

Geometria



GEOMETRY

Size	S	M	L	XL
A Seat Tube Length	390 mm	420 mm	470 mm	510 mm
B Top Tube Length	590 mm	611mm	632 mm	650 mm
C Bottom Bracket Drop	-65 mm	-65 mm	-65 mm	-65 mm
D Bottom Bracket Height	305 mm	305 mm	305 mm	305 mm
E Chainstay Legth	430 mm	430 mm	430 mm	430 mm
F Seat Tube Angle, Actual	73°	73°	73°	73°
G Seat Tube Angle, Effective	74.5°	74.5°	74.5°	74.5°
H Head Tube Angle	68.5°	68.5°	68.5°	68.5°
I Fork Offset	44 mm	44 mm	44 mm	44 mm
J Wheelbase	1107 mm	1128 mm	1150 mm	1170 mm
K Head Tube Length	85 mm	90 mm	100 mm	115 mm
L Reach	425 mm	444 mm	463 mm	477 mm
M Stack	598 mm	602 mm	611 mm	625 mm