# CRAFTY R, BLACK/ORANGE, 2021

*obj. č: 010.21247*




Sugerowana cena

**31.199 zł**

Aktualna cena

**27.599 zł**

## Specyfikacje techniczne

**produkowane rozmiary**
S 380mm / M 420mm / L 450mm / XL 490mm

**waga**
24,9 Kg

**rama**
Crafty 6061 Alloy Stealth Evo, e-Bike Optimized Zero Suspension System, 150mm travel, Forward Geometry, internal removable battery with integrated alloy cover, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers.

**widelec**
Fox 38 29 Float FIT GRIP EVOL Performance, 160mm, e-bike tuned, tapered steerer tube, Boost 15x110mm axle, 44mm offset. Settings: 3 positions with micro adjust compression, low-speed rebound, air preload

**stery**
Onoff Saturn tapered for 1-1/8 to 1-1/2 head tube, ACB sealed bearings, top 41x30.2x7x45x45, bottom 51.9x40x8x45x45

**przerzutka**
Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1

**manetki**
Sram Trigger NX Eagle, 12s, X-Actuation 1:1, single click

**klamki hamulca**
Sram G2 R, tool-free reach adjust

**uchwyty**
Race Face Aeffect ebike, 165mm

**kierownica**
Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 780mm, 9 backsweep, 5 upsweep, 31.8mm barbore Onoff Desert, 1lock-on, 135mm, sizes: S/M L/XL

**mostek**
Onoff Sulfur FG 30mm 0, 6061 forged alloy, 31.8mm barbore

**sztyca**
Onoff Pija dropper internal, diameter 31.6mm, S size: 387x125mm, M size: 425x150mm, L/XL size: 465x170mm

**siodełko**
SDG BEL-AIR 3.0, EVA foam, steel rails

**piasta przednia**
DT 370, Boost 15x110mm, IS 6 bolts

**tylna piasta**
DT 370, Boost 12x148mm, 3 Pawl system, IS 6 bolts

**łańcuch**
Sram SX Eagle, 12s, Powerlock

**kaseta**
Sram PG-1210, 11-50T, 12s

**szprychy**
DT Hybrid SP, straightpull

**rafki**
DT Swiss H1900 Spline 29, 30mm internal width, sleeved aluminum, tubeless ready, 28 spokes

**obudowa**
Maxxis Minion DHF 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead

**zamówienie numer**
010.21247

**amortyzator**
Fox Float DPX2 LV EVOL Performance, 205x65mm. Settings: compression 3 positions lever, low-speed rebound, air preload. Trunnion top mount, 25x10mm bottom bushings

**przedni hamulec**
Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads

**tylny hamulec**
Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads

**owijka**
Maxxis Minion DHR II 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead


**regulacja amortyzatora**
CEC001 compression, Medium rebound, 0.2 volume spacer

**korba**
Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD

**mocowanie przerzutki**
Mondraker M068

**silnik + akumulator**
Bosch Performance Line CX Cruise (25Km/h) GEN4, computer Bosch Kiox, Bosch Powertube 625Wh

## Geometria




**GEOMETRY**

| Size | | S | M | L | XL |
|---|---|---|---|---|---|
| A | Seat Tube Length | 380 mm | 420 mm | 450 mm | 490 mm |
| B | Top Tube Length | 605 mm | 625 mm | 650 mm | 670 mm |
| C | Bottom Bracket Drop | -25 mm | -25 mm | -25 mm | -25 mm |
| D | Bottom Bracket Height | 350 mm | 350 mm | 350 mm | 350 mm |
| E | Chainstay Legth | 455 mm | 455 mm | 455 mm | 455 mm |
| F | Seat Tube Angle, Actual | 73.5° | 73.5° | 73.5° | 73.5° |
| G | Seat Tube Angle, Effective | 76° | 76° | 76° | 76° |
| H | Head Tube Angle | 65.5° | 65.5° | 65.5° | 65.5° |
| I | Fork Offset | 44 mm | 44 mm | 44 mm | 44 mm |
| J | Wheelbase | 1225 mm | 1245 mm | 1265 mm | 1285 mm |
| K | Head Tube Length | 110 mm | 110 mm | 130 mm | 130 mm |
| L | Reach | 450 mm | 470 mm | 490 mm | 510 mm |
| M | Stack | 622 mm | 622 mm | 640 mm | 640 mm |