

PLAY 20, ORANGE/BLACK, 2023

obj. č: 010.23207



Specyfikacje techniczne

produkowane rozmiary One size: 260mm	rama Play 20 6061 Alloy Stealth evo, hydroformed tubing, integrated internal non-removable battery, Tapered head tube, HHG internal cable routing, BSA bottom bracket, QR 9mm rear axle, 1x drivetrain compatible
widelec MDK 20 Kid, Rigid alloy Stealth stanchions, Post Mount disc brake mount	stery Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°
przerzutka Microshift M26S, 9s, short cage	manetki Microshift Mezzo TS39-9, 9s
klamki hamulca Sram Level, tooled reach adjust, lever pivot bushings	uchwyty Samox DM 28T steel, 114mm
support BSA, 73mm	kierownica MDK XC 1.0, 6061 alloy, rise: 25mm, width: 580mm, 9° backsweep, 5° upsweep, 31.8mm barbare
mostek Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbare	sztyca MDK XC 0-R, 6061 T6 Alloy, diameter 31.6mm, length 250mm
siodełko MDK Play 20	piasta przednia Formula DC20LW, 9x100mm, cup cone ball bearings, IS 6 bolts
tylna piasta Mahle-Ebikemotion X-35	łańcuch Sram PC951 9s, Powerlock
kaseta Microshift Mezzo 11-34T, 9s	szprychy CN round stainless steel
rafki MDK-XP1 20 TLR, 25mm internal width, tubeless ready, 32 spokes	obudowa Kenda Booster 20x2.4 single compound 30TPI, wire bead
zamówienie numer 010.23207	gripy Onoff Twin, 1lock-on
przedni hamulec Sram Level, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad	tylny hamulec Sram Level, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad
korba 28T, steel	mocowanie przerzutki Mondraker M073
silnik + akumulator Mahle-Ebikemotion X-35, Mahle-Ebikemotion Internal 250Wh, Mahle-Ebikemotion	

Galeria

