

SUPERFOXY R, SILVER/BLACK/RED, 2021

obj. č: 010.21097



Sugerowana cena

23.919 zł

Specyfikacje techniczne

produkowane rozmiary S 380mm / M 420mm / L 470mm / XL 510mm	waga 15,8 Kg
rama SuperFoxy 29 6061 Alloy Stealth Evo, hydroformed tubing, Zero Suspension System, 160mm travel, Forward Geometry, one piece Monoblock upper link, SuperBoost 12x157mm rear axle, tapered head tube, 73mm BSA bottom bracket, dedicated 1x drivetrain design, telescopic seatpost internal routing, Max. capacity sealed bearings, ISCG 05	widelec Fox 38 29 Float FIT GRIP EVOL Performance, 170mm, tapered steerer tube, Boost 15x110mm axle, offset 44mm. Settings: 3 positions with micro adjust compression, low-speed rebound, air preload
stery Onoff Saturn tapered for 1-1/8 to 1-1/2 head tube, ACB sealed bearings, top 41x30.2x7x45x45, bottom 51.9x40x8x45x45	przerzutka Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1
manetki Sram Trigger GX Eagle, 12s, X-Actuation 1:1	klamki hamulca Sram Code R, tool-free reach adjust
uchwyty Truvativ Descendant 7K Eagle, SuperBoost, DUB axle, Direct mount chain ring, S/M size 170mm, L/XL size 175mm	support Sram DUB BSA, sealed bearings, 73mm
kierownica Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 780mm, 9 backsweep, 5 upsweep, 31.8mm barbore Onoff Twin, 1lock-on, 135mm	mostek Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbore
szttyca Onoff Pija dropper internal, diameter 31.6mm, S size: 337x100mm, M size 387x125mm, L size: 425x150mm, XL size: 465x170mm	siodełko SDG BEL-AIR 3.0, LPU foam, steel rails
piasta przednia DT 370, Boost 15x110mm, IS 6 bolts	tylna piasta DT 370, SuperBoost 12x157mm, 3 Pawl system, IS 6 bolts, XD freehub
łańcuch Sram NX Eagle, 12s, Powerlock	kaseta Sram XG-1275, 10-52T, 12s
szprychy DT Champion, straightpull	rafki DT Swiss E1900 Spline 29, 30mm internal width, sleeved aluminum, tubeless ready, 28 spokes
obudowa Maxxis Minion DHF 29x2.5 WT, tubeless ready, 3C MAXX TERRA compound, EXO+ protection, 120TPI, folding bead	zamówienie numer 010.21097
amortyzator Fox Float X2 EVOL Performance, 205x65mm. Settings: Open/Firm, low-speed compression, low-speed rebound, air preload. Trunnion top mount, 22.2x10mm bottom bushings	przedni hamulec Sram Code R, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads

tylny hamulec
Sram Code R, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads


regulacja amortyzatora
Medium compression, medium rebound, air volume

mocowanie przerzutki
Mondraker M068

owijka
Maxxis Minion DHR II 29x2.4 WT, tubeless ready, 3C MAXX TERRA compound, EXO+ protection, 120TPI, folding bead

korba
32T, CNC-machined alloy, X-SYNC 2

Geometria



GEOMETRY

Size	S	M	L	XL
A Seat Tube Length	380 mm	420 mm	470 mm	510 mm
B Top Tube Length	605 mm	625 mm	650 mm	670 mm
C Bottom Bracket Drop	-20 mm	-20 mm	-20 mm	-20
D Bottom Bracket Height	350 mm	350 mm	350 mm	350 mm
E Chainstay Legth	445 mm	445 mm	445 mm	445 mm
F Seat Tube Angle, Actual	71°	71°	71°	71°
G Seat Tube Angle, Effective	76°	76°	76°	76°
H Head Tube Angle	65°	65°	65°	65°
I Fork Offset	44 mm	44 mm	44 mm	44 mm
J Wheelbase	1224 mm	1245 mm	1273 mm	1293 mm
K Head Tube Length	100 mm	110 mm	130 mm	130 mm
L Reach	450 mm	470 mm	490 mm	510 mm
M Stack	621 mm	621 mm	639 mm	639 mm