

chybí obrázek

Sugerowana cena

0 zł

Specyfikacje techniczne

produkowane rozmiary S , M , L , XL	waga 13,60
rama Foxy 27,5 Stealth Air full Carbon Structure, Zero Suspension System, Forward Geometry, aluminium CSC upper link with carbon bridge, Boost 12x148mm rear axle, BSA 73mm bottom bracket, dedicated 1x drivetrain design, Tapered head tube, HHG internal cable routing, Enduro MAX sealed bearings, mudguard for shock, ISCG 05, custom chainstay protector, carbon fabric protector in the diagonal tube, 150mm of travel. *Optional Geometry Kit.	widelec Rockshox Revelation RC Solo Air, 150mm, Tapered head tube, 15x110mm axle. Settings: rebound, compression adjustment at low-speed to lock, air preload.
stery Onoff Saturn Tapered for 1-1/8" -> 1/5" head tube. Top bearing 41x30.2x7x45?x45?, bottom 51.9x40x8x45?x45?.	przerzutka Sram NX Type 3 with Roller Bearing Clutch and Cage Lock, long cage, X-Horizon system.
manetki Sram Trigger NX1, 11s. Zero Loss technology, Exact actuation.	klamki hamulca Shimano MT-500, small lever for braking with 2 fingers.
uchwyty SRAM NX16000 series aluminium, 24mm axle, chain ring with Direct Mount, standard Boost, 170mm crank arm length in S/M size and 175mm in L/XL size.	support SRAM GXP XR, sealed bearings, 73mm.
kierownica Mondraker aluminium 6061 double-Tapered. Exclusive design for Foxy Carbon R, height 20mm, width 780mm, 9° backsweep, 5° upsweep, diameter 31.8mm.	mostek Onoff Stoic FG 30mm. Molded aluminium 6061, handlebar diameter 31.8mm.
pedały /	szttyca Onoff Pija Dropper 31.6mm, internal hose guide. Size S: 337x100mm, size M/L/XL: 387x125mm.
siodełko Mondraker Foxy Carbon R exclusive design.	piasta przednia MDK DC511 15x110mm, sealed bearings, IS 6 bolts mount.
tylna piasta MDK GW 12x148mm, sealed bearings, IS 6 bolts mount.	łańcuch SRAM PC-1110 11s.
kaseta Sunrace CSMS8, 11-46T, 11s.	szprychy CN round stainless steel.
rafki MDK-EP1 27,5 TLR ASY, internal width 27mm, tubeless ready, 32 spokes.	obudowa Maxxis Ardent 27,5x2.40. Single compound, 60 TPI, wire.
zamówienie numer 010.18071	amortyzator RockShox Deluxe RL Debonair. Settings: rebound, compression (2 positions: Open/Pedal), air preload. 205x62.5mm. Trunnion top mount, 22.2x10mm bottom bushes.
przedni hamulec Shimano MT-500, Servo Wave technology, aluminium clamp, mineral oilresin pads, 180mm single-piece disc with 6 holes.	tylny hamulec Shimano MT-500, Servo Wave technology, aluminium clamp, mineral oilresin pads, 180mm single-piece disc with 6 holes.

owijka
Maxxis Ardent 27,5x2.40. Single compound, 60 TPI, wire.

korba
32T, steel, X-SYNC 1x11 technology.

inne
* Optional Geometry Kit: chainstay adapters to 435mm. Headset cups +/- 1°.

regulacja amortyzatora
Medium compression, medium rebound, lock out firm 430, 2 internal reducers.

mocowanie przerzutki
Mondraker M071.