

chybí
obrázek

Sugerowana cena

0 zł

Specyfikacje techniczne	
produkowane rozmiary S , M , L , XL	rama e-Crafty 27,5 6061 Alloy Stealth Evo, Bosch Performance CX system with integrated removable battery, Zero Suspension System, Forward Geometry, Boost 12x148mm rear axle, Tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, exclusive plastic motor covers, shock mudguard integrated in the swingarm, travel 140mm.
widelec RockShox Yari 27.5+ RC Solo Air Boost tapered 160mm	stery Onoff Saturn Tapered for 1-1/8" -> 1/5" head tube. Top bearing 41x30.2x7x45?x45?, bottom 51.9x40x8x45?x45?.
przerzutka Sram GX long cage, Exact actuation	przerzutka /
manetki Sram Trigger GX, 10s. Zero Loss technology, Exact actuation	klamki hamulca SRAM Level T, brake lever reach adjust, 2 bolts clamp Matchmaker compatible, ambidextrous lever mount.
support /	kierownica Mondraker custom design 1.0 780mm.
mostek Onoff Stoic FG 30mm. Forged 6061 alloy, 31.8mm barbore.	sztyma Onoff Pija Dropper 31.6mm, internal hose guide. Size S: 337x100mm, size M/L/XL: 387x125mm.
siodełko Exclusive Mondraker E-mtb design	piasta przednia MDK Pro II 15x110mm.
tylna piasta MDK Pro II 12x148mm.	łańcuch Sram PC-1031 10s
kaseta Sunrace CSMCS3 11-42T 10s.	szprychy CN stainless.
rafki NEW MDK-EP1 27,5 Asy 35 TLR wheelset.	obudowa Maxxis Minion DHF 27,5x2.8, tubeless ready, Dual compound, Exo Protection, 60TPI, folding.
amortyzator RockShox Superdeluxe R Debonair. Settings: Rebound, air preload. 205x62.5mm. Trunnion top mount, 22.2x10mm bottom bushes.	przedni hamulec Sram Level T 200mm, centerline 6 bolts one-piece rotor, organic pads
tylny hamulec Sram Level T 200mm, centerline 6 bolts one-piece rotor, organic pads	owijka High Roller 27 II,5x2.8, tubeless ready, Dual compound, Exo Protection, 60TPI, folding.
regulacja amortyzatora Medium compresion, medium rebound, 2 internal reducers.	