

Sugerowana cena

0 zł

Specyfikacje techniczne

produkowane rozmiary S , M , L , XL	**waga** 10,1 kg
rama Podium 29er Stealth Air Carbon, redesigned internal structure , Integrated Stem Technology (IST EVO), XC Forward Geometry, PF30 bottom bracket, Tapered head tube, HHG internal cable routing ,Boost rear axel 12x148mm, Flatmount brake compatible, steel chain protector.	**widelec** RockShox SID 29 RL Solo Air 100mm, tapered head tube, Boost 15x110mm axel, 30mm aluminium stanchions. Settings: Rebound, low-speed compression until lock-out, air preload
stery Onoff Titan internally Tapered for 1-1/8” -> 1/5” head tube. Top bearing 41.8x30.5x8x45?x45?, bottom 51.9x40x8x45?x45?.	**przerzutka** Sram GX Eagle Type 3 with Roller Bearing Clutch and Cage Lock, 1x12s, long cage, X-Horizon system.
manetki Sram Trigger GX Eagle 12s, X-Actuation, Zero Loss Technology.	**klamki hamulca** SRAM Level T, brake lever reach adjust, 2 bolts clamp Matchmaker compatible, ambidextrous lever mount.
uchwyty Truvativ Stylo 6k Eagle, 6000 series aluminium crank arms, 30mm axle, chain ring with Direct Mount, standard Boost, 170mm crank arm length in S size and 175mm in M/L/XL size.	**support** Rotor 4630, PF30, sealed bearings.
kierownica Onoff Peak Carbon 0.2. 4.8mm rise, 710mm width, 9? backsweep, 0? upsweep, 31.8mm barbore	**mostek** Stealth Carbon Integrated, sizes S/M: 85mm, sizes L/XL: 100mm length
pedały /	**sztyca** Onoff Peak Carbon 0-R. 27.2mm. Diameter. 400mm length
siodełko Mondraker design.	**piasta przednia** Mavic, Boost 15x110mm axel, sealed bearings, IS 6 bolts mount.
tylna piasta Mavic, Boost 12x148mm axel, sealed bearings, TS-2 XD freehub, IS 6 bolts mount.	**łańcuch** SRAM GX Eagle 12s.
kaseta SRAM XG-1275 10-50T, XD freehub for 12s.	**szprychy** Mavic steel, straight pull, profiled, double butted.
rafki Mavic Crossmax Light 29, Tubeless Ready, 22mm internal width, asymetric, hookless, 24 spokes.	**obudowa** Maxxis Ikon 29x2.20, 60 TPI, wire.
zamówienie numer 010.18155	**amortyzator** /
przedni hamulec Sram Level T 160mm, centerline 6 bolts one-piece rotor, organic pads	**tylny hamulec** Sram Level T 160mm, centerline 6 bolts one-piece rotor, organic pads
owijka Maxxis Ikon 29x2.20, 60 TPI, wire.	**korba** 32T Direct Mount, aluminium, X-SYNC 2.
mocowanie przerzutki Mondraker M068.	**inne** Boost 12x148mm rear axle.