

chybí obrázek

Sugerowana cena

0 zł

Specyfikacje techniczne

produkowane rozmiary S , M , L , XL	waga 13,70
rama Dune 27,5, Stealth full Carbon, Zero Suspension System, Forward Geometry, carbon upper link, 12x142mm rear axle, 73mm BSA bottom bracket, MAX. capacity sealed bearings, internal cable routing, ISCG 05, dedicated 1x drivetrain design, ISCG 05 carbon protector, carbon mudguard. 160mm travel. *Optional Geometry kit.	widelec Fox 36 27,5 Float Grip EVOL Performance 170mm, Lever with 3 positions plus intermediate positions in low/high-speed compression. Tapered head tube, 15x110mm axle. Settings: rebound, high/low-speed compression to lock, air preload.
stery Onoff Titan internally Tapered for 1-1/8" -> 1/5" head tube. ACB sealed bearings, top 41.8x30.5x8x45?x45?, bottom 51.9x40x8x45?x45?.	przerzutka Sram GX1 Type 2.1 with Roller Bearing Clutch and Cage Lock, 1x11s aluminium, long cage, X-Horizon system.
przerzutka /	manetki Sram Trigger NX1, 11s. Zero Loss technology, Exact actuation.
klamki hamulca Sram Guide R, tools-free Reach adjust, ambidextrous lever mount.	uchwyty SRAM NX16000 series aluminium, 24mm axle, chain ring with Direct Mount, 170mm crank arm length in S/M size and 175mm in L/XL size.
support SRAM GXP XR, sealed bearings, 73mm.	kierownica Mondraker double butted 6061 aluminium, Exclusive Dune R design, 1" rise, 780mm width, 9? backsweep, 5? upsweep, 31.8mm barbare
mostek Onoff Stoic FG 30mm. 6061 forged aluminium. 31.8mm barbare	pedały /
sztyca Onoff Pija Dropper 31.6mm, internal hose guide. Size S: 337x100mm, size M/L/XL: 387x125mm.	siodełko SDG Fly MTN TI, High-density PU, chromium rail, cordura sides protection
piasta przednia MDK DC511 15x110mm, sealed bearings, IS 6 bolts mount	tylna piasta MDK GW 12x142mm, sealed bearings, IS 6 bolts mount
łańcuch SRAM PC-1110 11s.	kaseta Sunrace CSMS8, 11-46T, 11s.
szprychy CN round stainless steel.	rafki MDK-EP1 27,5 TLR ASY, internal width 27mm, tubeless ready, 32 spokes.
obudowa Maxxis High Roller II 27'5 x 2.3 Tubeless Ready, Dual compound, Exo protection, 60TPI, folding	zamówienie numer 010.18099
amortyzator Fox Float X2 Performance. Settings: high-speed compression, high-speed rebound, air preload. 216x63mm. Bushings 22.2x10mm upper / 16.2x10mm lower.	przedni hamulec Sram Guide R 200mm, lightweight 4-piston dual-diameter caliper, centerline 6 bolts one-piece rotor, semi-metallic pads
tylny hamulec Sram Guide R 180mm, lightweight 4-piston dual-diameter caliper, centerline 6 bolts one-piece rotor, semi-metallic pads	owijka Maxxis High Roller II 27'5 x 2.3 Tubeless Ready, Dual compound, Exo protection, 60TPI, folding

regulacja amortyzatora
Light compression, light rebound, air volume spacers 0.3x4.

mocowanie przerzutki
Mondraker M065

korba
32T, steel, X-SYNC 1x11 technology.

inne
*Optional Geometry Kit: chainstay adapters to 440mm.
Headset cups de +/- 1°. Brake adaptors to 440mm.